

THE NECESSITY OF AN INTELLIGENT RECHARGE SYSTEM IN THE MASSIVE DEVELOPMENT OF ELECTRIC VEHICLES

SUAREZ-FORERO Maria-Juliana, Renault Group – IFP Energies Nouvelles – Université Paris Dauphine, majsuarezf@gmail.com

GEOFFRON Patrice, Université Paris Dauphine, patrice.geoffron@dauphine.psl.eu

LANTZ Frédéric, IFP Energies Nouvelles, frederic.lantz@ifp.fr

NICOLAS Pierre, Renault Group, pierre.nicolas@renault.com

Overview

Transportation and electricity generation sectors are responsible of 23% and 40% of energy related CO₂ emissions respectively. Road transport, including cars, motorcycles and buses, realise 16% of CO₂ emissions by their own. Concerning the power sector, coal power plants are the main emitters, responsible of 29% of CO₂ emissions. Europe, concerned and worried about the climate change, expects to reach the carbon neutrality by 2050.

To do so, EU defined specific targets for renewable energies (REn) deployment through the *Renewable Energy Directive*. This renewable energy target was updated to 40% in the new legislation package released on July 14th 2021 by the European Commission. By this date, it announced its new project to mitigate the climate change *Fit for 55*, and set the ambitious target of reducing 55% of the greenhouse gas emissions by 2030 (compared to 1990 levels). A continuous and important evolution of particular vehicles, and of transportation in general was established as well. In this current legislation, the European Commission expects to ban the sales of new internal combustion engine cars by 2035, this means that even hybrid cars must be set apart from the roads, letting 100% of the particular vehicles market to alternative fuel systems. To achieve this goal within the expected term, by 2030 particular vehicles are expected to have reduced 55% of their CO₂ emissions.

The Vehicle Grid Integration (VGI) refers to the set of technologies, services and policies that create a link between transport with its electric vehicles (EV) and the power systems. This combination between transport and REn supply is important because with a massive adoption of EV and with no control over the recharge, the power grid risks intermitent faillures when it will not be able to supply the required instantaneous power. A smart charge system becomes necessary.

Considering that the development of REn creates a flexibility requirement for the grid operation, the integration of EV in the power system is two-fold in the decarbonization goals: to reach the objective of getting a cleaner mobility and to assist adequacy and reliability in more renewable electricity mixes.

Nevertheless, a proper integration with a smart charging system requires synergy between the concerned parties including grid operators, governments, car makers and car owners as well as a good understanding of the main factors of the recharge system that could impact the power grid and that therefore are essential for the VGI e.g. the different chargers power or the charge behaviours. A technical and economic analysis of these components is the core of this paper.

Methods

In this context of the economic activity, different organizations estimate that there will be some millions of EV on the roads in a close future. The adoption of a significant EV fleet entails a new electric load during the recharge phases. We propose a decentralized algorithm that responds to the future concerns of an EV fleet and that improves the current electricity mix dynamics. The general concept is to create a virtual battery composed by the sum of a part of each EV battery. This cumulated capacity is managed in an optimal way, which directly manages the EV charge without aggregator. It will support the bulk power system for filling demand valleys through the smart charging and for shaving demand peaks through Vehicle-to-Grid (V2G).

We present the development and implementation of the VGI algorithm composed by a set of equations that respond to an optimal dynamic behaviour. Optimization is done over one week with the aim of taking into account the variations on the power system linked to regional behaviors (e.g. less consumption during weekend than during week days). The algorithm can receive and use different parameters as input signal e.g. electricity tariffs or CO₂ emissions. For our case study we use a residual demand signal that is calculated as the total electricity demand subtracting photovoltaics and wind turbines electricity production. We consider conventional power plants generation and international flows are fixed. This choice is made since we find a close relationship between residual demand with electricity market prices as well as a close relationship between residual demand and CO₂ emissions. The algorithm

output has two components: the state of the charge (SOC) that will be reached by the battery and a proportional factor that will regulate the amount of the appealed power at each time step.

Next, we implement the smart charging algorithm in a VGI simulator. This tool is able to reproduce the charging dynamics of an important EV fleet during one week in an hourly step. For the simulation we use real data from a national statistical survey in France. The objective of the simulator is to understand the parameters that could have an important impact during the integration of EV in the power grid considering different car owners behaviors. Some of the parameters of the simulator are the chargers power, the chargers locations, charging thresholds (the SOC at which a car owner plugs its EV), etc.

Results

The simulation of a real vehicle fleet applying a smart charging algorithm is a powerful tool to understand the main EV challenges. Such simulation is useful for all stakeholders: grid operators, governments, car makers and academics. A first outcome is the technical one. We consider that smart charging for balancing the power grid is done through low power chargers (home and work chargers mainly). We calculate the real driving consumptions and therefore, the real electricity supply requirements for each day of the week. We use a typical labouring week. Through the simulation we can estimate the impact of different proportions between chargers power, the impact of using or not the EV as work transport and we can consider the fact of preparing a long trip for the next day for example.

A second outcome is the economic one. For estimating the surplus related to VGI we consider two different income sources. The first one is the distribution grid deferral. An intelligent and controlled EV charge could contribute to reduce the investment requirements since the existent grid would be used in an optimal way. Through VGI the distribution system operator (DSO) can supply the EV fleet electricity demand while keeping the appealed powers into ranges that do not need or that need just a small reinforcement. Our next income source estimation is the recharge cost. In this analysis we do not consider taxes neither the grid related costs. We use spot market prices to calculate the real cost of the EV fleet recharge.

Conclusions

Through the simulation of an optimized charge that parameterizes influential variables, we have technical and economics results. They are both important for guiding policies and for preparing the terrain of a future electric mobility. By way of optimization and simulation, we create possible scenarios of EV charge that represent real drivers behaviours. The visualization of the impact on the power grid is expected to ease EV integration for all VGI actors. And finally, with the results of this work, we indulge in the question of how could this surplus benefit each one of these actors.

References

Do, L. P. C., Lyócsa, Š., & Molnár, P. (2021). Residual electricity demand: An empirical investigation. *Applied Energy*, 283, 116298.

European Commission. (2021). *Fit for 55*. <https://www.ecologie.gouv.fr/fit-55-nouveau-cycle-politiques-europeennes-climat>

Szinai, J. K., Sheppard, C. J. R., Abhyankar, N., & Gopal, A. R. (2020). Reduced grid operating costs and renewable energy curtailment with electric vehicle charge management. *Energy Policy*, 136.